DEXT 3.0

REDEFINING HIGH CEILING EXCELLENCE

SPECIFICATION SHEET
STATIC WHITE

Housing
Diameter : Ø17.86" | Height : 12.5" | Weight : 27 lbs

Material
Housing : High Pressure Die-Cast Aluminum
Lens : Clear Polycarbonate

Power Input
300W, 400W, 500W | 120-277V

Lumen Output
45,000lm (300W), 59,600lm (400W), 74,000lm (500W)

Dimming
Standard 0-10V : Dims to 10%

Color Quality	Rated Life
CRI 85	> 100,000 Hours (L70)

Finish

Black White

Color Temperature

3000K 3500K 4000K 5000K

Optics

30° 50° Wide

Mounting

Bracket Stem Mount Uplight Stem Adjustable Cable

Warranty
5 Year limited warranty

Listing

CE UKCA ETL Intertek IK10

Bright. Tough. Efficient.

Introducing Dext 3.0, a compact yet robust high ceiling luminaire that delivers up to 74,000 lumens with nearly 150 lm/W efficacy. Designed for performance and long-term value, it handles harsh environments with ease. Optional features include a glare-reducing shroud, IK10-rated wire guard, and IP65 outdoor configuration—making Dext 3.0 a durable and also an ideal choice for those seeking both quality and value.

METEOR

meteor-lighting.com

DEXT 3.0

REDEFINING
HIGH CEILING EXCELLENCE

METEOR

SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

Use our online product configurator to quickly assemble fixture specifications

DS3	MODEL	**DEXT 3.0 SERIES**		
	WATTAGE	**300** 300W	**400** 400W	**500** 500W
	CCT / CRI	**308** 3000K / CRI 85 **508** 5000K / CRI 85	**358** 3500K / CRI 85	**408** 4000K / CRI 85
UNV	VOLTAGE	**UNV** 120 – 277V		
	DIMMING	**NOD** Non-Dimming	**STV** Standard 0-10V dims to 10%	
	BEAM ANGLE	**30** 30°	**50** 50°	**WD**[1] Wide
	FINISH	**BLK** Black	**WHT** White	
	MOUNTING	**BRK** Bracket **UST2**[2] Uplight Stem 2ft **SAD10** Sloped Adjustable Cable 10ft	**ST2** Stem 2ft **UST4**[2] Uplight Stem 4ft	**ST4** Stem 4ft **AD10** Adjustable Cable 10ft
	ACCESSORIES	**ALS**[3] Aluminum Shroud	**WG**[3,4] Wire Guard (IK10 Rating)	

CLEAR FORM

[1] *WD option reduces delivered lumens by ~20%*
[2] *UST is not compatible with ALS*
[3] *Option is not compatible with Diffuser*
[4] *WG option reduces delivered lumens by ~14%, and WG is not compatible with ALS*

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

REV 11062026

DEXT 3.0

REDEFINING
HIGH CEILING EXCELLENCE

METEOR

TECHNICAL DETAILS

Electrical

- 45,000lm (300W), 59,600lm (400W), 74,000lm (500W)
- Power Input : Universal (120-277V)
- Operating Temperature : -22°F~113°F
- Surge Protection : Built-in is 4KV

LED Features

- Color Temperature : 3000K, 3500K, 4000K, 5000K
- CRI 85
- Long lasting LED luminaire tested under TM21 lumen
- maintenance L70 @ 100,000 Hrs

Optics

- Precision molded high transmittance clear PC lens
- Beam Angle : 30°, 50°, WD

Advanced Dimming

- Proprietary VX Driver™ is integrated across all dimming options, delivering video flicker-free performance and full compliance with IEEE 1789.
- Standard 0-10V : Dims to 10%

Housing

- Diameter : Ø17.86"
- Height : 12.5"
- Material : High Pressure Die-Cast Aluminum, PC Lens
- Weight : 27 lbs

Mounting

- Bracket
- Stem 2ft or 4ft; 45° Swivel Canopy Included
- Uplight Stem 2ft or 4ft
- Adjustable Cable 10ft
- Sloped Adjustable Cable 10ft

Warranty

- 5-year limited warranty

Listing

- ETL Damp Location Listed
- CE
- UKCA
- IK10 (With Wire Guard)

PERFORMANCE SUMMARY*

Delivered Lumens				
CCT/WATTAGE	3000K	3500K	4000K	5000K
300W	42,500lm	43,100lm	43,700lm	45,000lm
400W	56,300lm	57,100lm	57,900lm	59,600lm
500W	70,000lm	71,000lm	72,000lm	74,000lm

**Beam Angle: 50° * Tolerance ±8%*

Current Consumption		
WATTAGE / VOLT	120V	277V
300W	2.78A	1.21A
400W	3.71A	1.61A
500W	4.62A	2A

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

REV 11062026

PHOTOMETRICS

Below is a typical photometric representation of the Dext 3.0 fixture. Please download IES files to ensure exact photometric value.



30°



50°



WD



30° with
Aluminum Shroud



50° with
Aluminum Shroud



WD with
Aluminum Shroud

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

DIMENSIONS









Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

ACCESSORIES

Aluminum Shroud



Wire Guard



Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

APPEARANCE

300W

400W

500W

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.