

DEXT MINI 10

SPECIFICATION SHEET
STATIC WHITE OUTDOOR

POWERFUL HIGH BAY LUMINAIRE
UP TO 14,000 LUMEN PACKAGE

Housing

Diameter : Ø10.7" | Height : 8.7" | Weight : 6.17 lbs

Material

Housing : High Pressure Die-Cast Aluminum

Lens : Clear Polycarbonate

Power Input

80W, 100W | 120-277V

Lumen Output

10,850 lm (80W), 13,550 lm (100W)

Dimming

Standard 0-10V : Dims to 10% with automatic shut-off when dimmed below 10%.

DALI : Dims to 10%

Color Quality

CRI 70, CRI 85

Rated Life

> 100,000 Hours (L70)

Finish



Black



White

Color Temperature



3000K



3500K



4000K



5000K

Optics



90°



Wide

Mounting



Stem
Mount



Adjustable
Cable



Bracket
Mount

Warranty

5 Year limited warranty

Listing




High Efficacy Led Luminaire For General Illumination And High Ceilings

High performance durable luminaire for high ceiling applications up to 20 ft.

Delivering exceptional light levels at high operating temperatures with a delivered lumen package range of 10,850 lm to 13,550 lm.

Outdoor, wet location listed.



METEOR

meteor-lighting.com

SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

<input type="text" value="DSM10"/>	MODEL	DEXT MINI 10		
<input type="text"/>	WATTAGE	80 80W	100 100W	
<input type="text"/>	CCT / CRI	308 3000K / CRI 85 507 5000K / CRI 70	358 3500K / CRI 85	408 4000K / CRI 85
<input type="text" value="UNV"/>	VOLTAGE	UNV 120 – 277V		
<input type="text"/>	DIMMING	NOD Non-Dimming	STV Standard 0-10V dims to 10%	DALI DALI dims to 10%
<input type="text"/>	BEAM ANGLE	90 90°	WD Wide	
<input type="text"/>	FINISH	BLK Black	WHT White	
<input type="text"/>	MOUNTING	BRK Bracket AD10 Adjustable Cable 10ft	ST2 Stem 2ft SAD10 Sloped Adjustable Cable 10ft	ST4 Stem 4ft
<input type="text"/>	RATING	OUT¹ Outdoor Rating	NAT² Natatorium Rating	
<input type="text"/>	ACCESSORIES	SPD³ Surge Protector CON⁵ Conical Lens	ALS13⁴ 13" Aluminum Shroud WG^{4,6} Wire Guard (IK10 Rating)	PCS11⁴ 11" PC Shroud FCS⁷ Field Cut Stem Adapter Kit

CLEAR FORM

¹ Outdoor Rating: Coating and wiring will be changed to high UV resistant and corrosion resistant materials for long-term operation in outdoor environments
² Natatorium Rating: Utilizes high corrosion-resistant materials for both coatings and sealants to prevent damage from long-term exposure to chlorine vapors
³ Surge protector for up to 10KV. Applicable for unstable mains or facilities using high power machineries
⁴ Only one option within this group can be specified
⁵ CON option reduces delivered lumens by ~15%, and CON is not compatible with ALS13, WG
⁶ WG option reduces delivered lumens by ~14%
⁷ FCS is not compatible with BRK, AD10, SAD10, OUT, NAT

TECHNICAL DETAILS

Electrical

- 10,850 lm (80W), 13,550 lm (100W)
- Power Input : Universal (120-277V)
- Operating Temperature : -22°F~113°F
- Surge Protection : Built-in is 4KV

LED Features

- Color Temperature : 3000K, 3500K, 4000K, 5000K
- CRI 70, CRI 85
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

Optics

- Precision molded high transmittance clear PC lens
- Beam Angle : 90°, Wide

Advanced Dimming

- Proprietary VX Driver™ is integrated across all dimming options, delivering video flicker-free performance and full compliance with IEEE 1789.
- Standard 0-10V : Dims to 10% with automatic shut-off when dimmed below 10%.
- DALI : Dims to 10%

Housing

- Diameter : Ø10.7"
- Height : 8.7"
- Material : High Pressure Die-Cast Aluminum, PC Lens
- Weight : 6.17 lbs

Mounting

- Stem 2ft or 4ft; 45° Swivel Canopy Included
- Adjustable Cable 10ft
- Bracket Mount
- Sloped Adjustable Cable 10ft

Warranty

- 5-year limited warranty

Listing

- ETL Wet Location Listed
- CE
- FCC
- IP65
- IK10

PERFORMANCE SUMMARY*

STD (Standard)				
CCT/WATTAGE	3000K	3500K	4000K	5000K
80W	10,000lm	10,320lm	10,650lm	10,850lm
100W	12,500lm	12,900lm	13,300lm	13,550lm

*Beam Angle: 90° *Tolerance ±8%

Current Consumption		
WATTAGE / VOLT	120V	277V
80W	0.67A	0.28A
100W	0.83A	0.36A

PCS (PC Shroud)				
CCT/WATTAGE	3000K	3500K	4000K	5000K
80W	9,500lm	9,800lm	10,100lm	10,310lm
100W	11,900lm	12,250lm	12,650lm	12,900lm


*Beam Angle: 90° *Tolerance ±8%

ALS (Aluminum Shroud)				
CCT/WATTAGE	3000K	3500K	4000K	5000K
80W	10,150lm	10,500lm	10,800lm	11,050lm
100W	12,700lm	13,100lm	13,500lm	13,800lm


*Beam Angle: 90° *Tolerance ±8%

PHOTOMETRICS


Below is a typical photometric representation of the Dext Mini fixture. Please download IES files to ensure exact photometric value.



STANDARD 90°



PC SHROUD 90°



ALUMINUM SHROUD 90°

ACCESSORIES

13" Aluminum Shroud






11" PC Shroud



11" PC Shroud + Conical Lens



DIMENSIONS



MOUNTING OPTIONS*

*Junction box not included

