REV 8 PRIME

SPECIFICATION SHEET
ARCHI-COLOR® W+RGB

QUIET CEILING DESIGN
HIGH LUMEN RECESSED DOWNLIGHT

Housing
Aperture : Ø9" | Oversize Trim : 9.13" | Ceiling Cutout : 8.25"
Maximum Ceiling Thickness : 1.5" | Height : 8.6"
Weight : 17.63 lbs/18.82 lbs (New Construction), 16.13 lbs (Retrofit)

Material
Housing : Forged Aluminum Heatsink
Reflector : Flow Forming Aluminum

Power Input
200W TypeA(White=100W, RGB=100W) | 120-277V
200W TypeB(White=150W, RGB=50W) | 120-277V

Lumen Output
13,250 lm (200W TypeA), 14,145 lm (200W TypeB)

Dimming
DMX : High resolution dims to 0.1%

Color Quality	**Rated Life**
CRI 85	> 100,000 Hours (L70)

Finish

Black White

Color Temperature

3000K + Archi-Color® W+RGB

Optics

45° 55° Wide

Warranty
5 Year limited warranty

Listing

Precision Engineered For High Performance.

8-inch aperture high lumen recessed downlight utilizing Meteor Lighting's proprietary Archi-Color® solution, that gives you True White light and unlimited RGB possibilities.

This product is compatible with all DMX control systems and follows ANSI E1.20 RDM protocol. You can now get white and RGB colors all from a single light source.



METEOR

meteor-lighting.com

REV 8 PRIME

QUIET CEILING DESIGN
HIGH LUMEN RECESSED DOWNLIGHT

METEOR

SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

	MODEL	**R8PN** REV 8 Prime with New Construction Frame	**R8PR** REV 8 Prime Retrofit	
	WATTAGE	**200A** White=100W/RGB=100W	**200B** White=150W/RGB=50W	
308C	CCT / CRI	**308C** 3000K + RGB / CRI 85 Archi-Color® W+RGB		
	VOLTAGE	**120** 120V	**277** 277V	
	DIMMING	**DMX** DMX dims to 0.1% (XLR Sockets)	**DMXR** DMX dims to 0.1% (RJ45 Sockets)	**DMXP** DMX dims to 0.1% (Terminal Block)
	BEAM ANGLE	**45** 45°	**55** 55°	**WD**[1] Wide (With Diffuser)
	FINISH*	**BLK** Black	**WHT** White	
	ACCESSORIES	**DF**[2] Diffuser **GR14**[4] Goof Ring 9.2" to 16" **SCA820**[5] Sloped Ceiling Adapter 18°-22°	**SPD**[3] Surge Protector **SCA810**[5] Sloped Ceiling Adapter 8°-12° **SCA825**[5] Sloped Ceiling Adapter 23°- 27°	**GR12**[4] Goof Ring 9.2" to 14" **SCA815**[5] Sloped Ceiling Adapter 13°-17° **2CPL**[6] 2' X 2' X 1" Custom Metal Ceiling Panel

CLEAR FORM

[1] *WD option reduces delivered lumens by ~20%*
[2] *DF option reduces delivered lumens by ~12% (~20% with WD)*
[3] *Surge protector for up to 10KV. Applicable for unstable mains or facilities using high power machineries*
[4] *GR includes new reflector and is not compatible with R8PN*
[5] *SCA is not compatible with R8PR*
[6] *2CPL is not compatible with R8PR, SCA810, SCA815, SCA820, SCA825*
* *Finish indicates trim only, with standard matte silver reflector*

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

REV 08042026

TECHNICAL DETAILS

Electrical

- 13,250 lm (200W TypeA | White = 100W, RGB = 100W)
  14,145 lm (200W TypeB | White = 150W, RGB = 50W)
- Power Input : 120V or 277V
- Operating Temperature : -40°F~112°F
- Surge Protection : Built-in is 4KV
- Power Factor Greater than 0.9

LED Features

- Color Temperature : 3000K+Archi-Color® W+RGB
- CRI 85
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

Optics

- Flow Forming Aluminum Reflector
- Beam Angle : 45°, 55°, Wide (With diffuser)

Advanced Dimming

- Proprietary VX Driver™ is integrated across all dimming options, delivering video flicker-free performance and full compliance with IEEE 1789.
- DMX : High resolution dims to 0.1% (Supports ANSI E1.20 RDM protocol)

New Construction Housing

- Aperture : Ø8.15" (New Construction), Ø9" (Retrofit)
- Height : 8.6"
- Weight : 17.63 lbs/ 18.82 lbs (New Construction), 16.13 lbs (Retrofit)
- Material : Forged Aluminum Heatsink
- Non-IC Rated, insulation must be kept >1ft from housing
- Oversize Trim : 8.46" (New Construction), 9.13" (Retrofit)
- Ceiling Cutout : 8.25"
- Maximum Ceiling Thickness : 1.5"
- Tool-less top access allows service from above and below
- Light engine, optics, and driver(s) accessible from below ceiling
- Goof Ring 14" : Aluminum, standard white finish; O. D. 16"; other size and finish available, please inquire

  *Note : C-Channel / Mounting Channels / T-Bar Hangers are purchased from a third party

Warranty

- 5-year limited warranty

Listing

- ETL Damp Location Listed
- FCC
- CE
- UKCA

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

REV 8 PRIME

QUIET CEILING DESIGN
HIGH LUMEN RECESSED DOWNLIGHT

METEOR

PERFORMANCE SUMMARY*

Lumen Performance				
200W TypeA	R	G	B	W
	615lm	4,075lm	480lm	8,080lm
200W TypeB	R	G	B	W
	220lm	1,700lm	210lm	12,015lm

Wattage				
Channel / Fixture Wattage	R	G	B	W
200W TypeA	33W	33W	33W	100W
200W TypeB	17W	17W	17W	150W

**Beam Angle: 45° * Tolerance ±8%*

Current Consumption		
WATTAGE / VOLT	120V	227V
200W	1.8A	0.9A

PHOTOMETRICS

Below is a typical photometric representation of the Rev 8 Prime fixture. Please download IES files to ensure exact photometric value.



45°



55°



WIDE

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

REV 08042026

DMX REQUIREMENTS

The Rev 8 Prime Archi-Color® fixture with DMX is a **four channel dmx** unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

	DMX Address			
Fixture	**Red Control (ex. X)**	**Green Control (ex. X+1)**	**Blue Control (ex. X+2)**	**White Control (ex. X+3)**
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

The fixture can be connected with RJ45 or XLR sockets. DMX cables **are not** included; please refer to compatible DMX cabling list for more information. The final fixture on each daisy chain should be terminated by the use of a DMX terminator purchased from a 3rd party or from Meteor.

CONNECTION	RJ45 (CAT5e)	5-PIN XLR
Common	WHITE/BROWN(PIN7) & BROWN (PIN 8)	PIN 1
Signal -	ORANGE (PIN 2)	PIN 2
Signal +	WHITE/ORANGE (PIN 1)	PIN 3
Spare	-	PIN 4
Spare	-	PIN 5



RJ45 Sockets



DMX IN DMX OUT

XLR Sockets

COMPATIBLE DMX CABLING LIST

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable **must not be used to carry DMX**. Network cable (Cat5, 5e or 6 cable) may be used to carry DMX in an installation; however special consideration must be given to shielding and termination. Under no circumstances should solid core cable like Cat5 be terminated into a screw down connector.

Meteor recommends the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed.

Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

DIMENSIONS

New Construction



Retrofit



Sloped Ceiling Adapter



Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.

DIMENSIONS

Goof Ring 12"





Goof Ring 14"





Custom Metal Ceiling Panel







Meteor Lighting reserves the right to make changes to this product for design and development improvements at any time without prior notice, and such modification shall be effective immediately. ©Meteor Illumination Technologies, Inc.