

ADVANCED HIGH CEILING

# DOT 3.5 - Warm Dim



New Dot 3.5 aperture micro cylinders with up to 1760 lumen output package. Smooth Dim to Dark compatibility with Ward Dim Color Tuning.

Quantity		Type	
Project		Note	

## Delivered

Warm Dim	1900K					2700K
0-10V CCT Voltage	0.7	2	4	6	8	10
15W	50 lm	180 lm	355 lm	560 lm	765 lm	1020 lm
25W	100 lm	255 lm	775 lm	980 lm	1345 lm	1760 lm

\*Tolerance±8%

### Electrical System

- 1020 lm (15W)
- 1760 lm (25W)
- Power Input: Universal (120-277V)
- Operating Temperature: 14°F~95°F
- Surge Protection: 2.5KV

### LED Technology

- Warm Dim™ (Tuning White: 1900K ↔ 2700K)
- 93 CRI
- UGR ≤19
- Beam Angle: 15°, 25°, 40°, 55°

### Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to dark
- TRIAC: Line-voltage phase control, dims to 1% (120V only)

### Housing

- Diameter: 3.5" (90mm)
- Height: 9.5" (242mm)
- Material: Aluminum
- Weight: 2.9 lbs

### Mounting

- Surface Mount
- Stem 2ft or 4ft
- Power Line Mount 2ft, 4ft, 6ft, 8ft, 10ft
- Cord Mount 10ft

### Warranty

- 5 year limited warranty

### Listing

- ETL Damp Location Listed
- CE



# DOT 3.5 - Warm Dim








## How To Specify:


**Ordering Example: DT3-25-WDIM-UNV-STV-15-BLK-BLK-SUM**

**4-5 weeks lead time on over 75% of specifications.**

Model	Wattage	CCT / CRI	Voltage	Dimming
DT3		WDIM	UNV	
DT 3	<b>15</b> 15W	<b>WDIM</b> 1900K - 2700K	<b>UNV</b> 120-277V	<b>STV</b> Standard 0-10V dims to 10%
DOT 3.5"	<b>25</b> 25W			<b>SPV</b> Superior 0-10V dims to dark
				<b>TRC</b> TRIAC dims to 1% (120V ONLY)

Beam Angle	Finish	Trim Finish	Mounting	Accessories
<b>15</b> 15°	<b>BLK</b> Black	<b>BLK</b> Black	<b>SUM</b> Surface Mount	<b>HC<sup>1</sup></b> Honey Comb
<b>25</b> 25°	<b>WHT</b> White	<b>WHT</b> White	<b>ST2</b> Stem 2ft	<b>SL<sup>2</sup></b> Solite Lens
<b>40</b> 40°	<b>SLV</b> Silver	<b>SLV</b> Silver	<b>ST4</b> Stem 4ft	
<b>55</b> 55°		<b>GLD</b> Gold	<b>PL2<sup>1</sup></b> Power Line Mount 2ft	<sup>1</sup> Please factor in change in lumen output of -30%
		<b>BL</b> Blue	<b>PL4<sup>1</sup></b> Power Line Mount 4ft	<sup>2</sup> Please factor in change in lumen output of -15%.
		 Black	<b>PL6<sup>1</sup></b> Power Line Mount 6ft	
		 WHT	<b>PL8<sup>1</sup></b> Power Line Mount 8ft	
		 SLV	<b>PL10<sup>1</sup></b> Power Line Mount 10ft	
		 GLD	<b>CM10</b> Cord Mount 10ft	
		 Blue	<b>WLM</b> Wall Mount	
			<sup>1</sup> Option only available with Remote Power	

## Dimensions




## Current Consumption

Wattage \ Volt	120V	277V
15W	0.14A	0.06A
25W	0.24A	0.11A

## Mounting Options

(Canopy Dimensions are the same for all)



## Remote Power

