

ADVANCED HIGH CEILING

Lance 4 – Single Sided



High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a lumen package range from 1,460 lm to 2,400 lm. Available in a variety of configurations, this IP 65 rated luminaire has a variety of optics to help make a bold architectural statement.

Quantity	Type
Project	Note

Electrical System

- 1620 lm (20W)
- 2400 lm (30W)
- Power Input: Universal (120-277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

LED Technology

- 2700K, 3000K, 3500K, 4000K, NA
- 85 CRI, 93 CRI
- Beam Angle: 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- TRIAC: Line-voltage phase control, dims to 1% (120V only)

Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

Warranty

- 5 year limited warranty

Listing

- ETL Wet Location Listed
- IP65



Lance 4 – Single Sided



How To Specify:

Ordering Example: LA4-D-20-408-UNV-SPV-35-BLK

4-5 weeks lead time on over 75% of specifications.

Model	Direction		Wattage		CCT / CRI		Voltage		Dimming	
LA4							UNV			
LA4	D	Down	20	20W	278	2700K / CRI85	UNV	120-277V	NOD	Non-Dimming
Lance 4	U	Up	30	30W	308	3000K / CRI85			STV	Standard 0-10V dims to 10%
					358	3500K / CRI85			SPV	Superior 0-10V dims to 1%
					408	4000K / CRI85			TRC	TRIAC dims to 1% (120V only)
					279	2700K / CRI93				
					309	3000K / CRI93				
					359	3500K / CRI93				

Beam Angle		Color		Finish		Accessories	
35	35	BLK	Black	STD	Standard	FW¹	Forward Throw
45	45	WHT	White	NAT	Natorium Rated	WW¹	Wall Wash 20°
60¹	60	GRY	Gray	MAR	Marine Finish	LL¹	Linear Lens
WIDE¹	WIDE	BRZ	Bronze			HC²	Honeycomb Louver
						SL³	Solite Lens
¹ Please factor in change in lumen output of -12%				¹ Please factor in change in lumen output of -20% ² Please factor in change in lumen output of -30%. ³ Please factor in change in lumen output of -15%.			

Lance 4 – Single Sided

Delivered Lumens*

CCT	Wattage	
	20W	30 W
4000K	1458 lm	2160 lm
3500K	1414 lm	2098 lm
3000K	1368 lm	2034 lm
2700K	1314 lm	1944 lm

Current Consumption

Wattage	Volt	
	120V	277V
20W	0.2A	0.09A
30W	0.3A	0.13A

*Tolerance±8%

Dimensions

