

ADVANCED HIGH CEILING

# Lance 4 - Single Sided



## High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a lumen package range from 1,460 lm to 2,400 lm. This IP 65 rated, single sided luminaire is available in a variety of configurations, and optics to help make a bold architectural statement.

Quantity		Type	
Project		Note	

### Electrical System

- 1620 lm (20W)
- 2400 lm (30W)
- Power Input: Universal (120-277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

### LED Technology

- 2700K, 3000K, 3500K, 4000K, NA
- 85 CRI, 93 CRI
- Beam Angle: 15°, 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

### Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- LTE: Hi-Lume 1% 2-wire LED Driver (120V forward phase only)

### Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

### Warranty

- 5 year limited warranty

### Listing

- ETL Wet Location Listed
- IP65



# Lance 4 - Single Sided



## How To Specify:

**Ordering Example: LA4-D-20-408-UNV-SPV-35-BLK**

**4-5 weeks lead time on over 75% of specifications.**

Model	Direction	Wattage	CCT / CRI	Voltage	Dimming
LA4				UNV	
LA4	<b>D</b> Down	<b>20</b> 20W	<b>278</b> 2700K / CRI85	<b>UNV</b> 120-277V	<b>NOD</b> Non-Dimming
Lance 4	<b>U</b> Up	<b>30</b> 30W	<b>308</b> 3000K / CRI85		<b>STV</b> Standard 0-10V dims to 10%
			<b>358</b> 3500K / CRI85		<b>SPV</b> Superior 0-10V dims to 1%
			<b>408</b> 4000K / CRI85		<b>LTE</b> Hi-Lume 1% 2-wire LED Driver (120V forward phase only)
			<b>279</b> 2700K / CRI93		
			<b>309</b> 3000K / CRI93		
			<b>359</b> 3500K / CRI93		

Beam Angle	Color	Finish	Accessories
<b>15</b> 15	<b>BLK</b> Black	<b>STD</b> Standard	<b>FW<sup>1</sup></b> Forward Throw
<b>30</b> 30	<b>WHT</b> White	<b>NAT</b> Natatorium Rated	<b>WW<sup>1</sup></b> Wall Wash 20°
<b>45</b> 45	<b>GRY</b> Gray	<b>MAR</b> Marine Finish	<b>LL<sup>1</sup></b> Linear Lens
<b>60<sup>1</sup></b> 60	<b>BRZ</b> Bronze		<b>HC<sup>2</sup></b> Honeycomb Louver
<b>WIDE<sup>1</sup></b> WIDE			<b>SL<sup>3</sup></b> Solite Lens
<sup>1</sup> Please factor in change in lumen output of -12%			<sup>1</sup> Please factor in change in lumen output of -20%
			<sup>2</sup> Please factor in change in lumen output of -30%.
			<sup>3</sup> Please factor in change in lumen output of -15%.

# Lance 4 - Single Sided

## Delivered Lumens\*

CCT	Wattage	
	20W	30 W
4000K	1458 lm	2160 lm
3500K	1414 lm	2098 lm
3000K	1368 lm	2034 lm
2700K	1314 lm	1944 lm

## Current Consumption

Wattage	Volt	
	120V	277V
20W	0.2A	0.09A
30W	0.3A	0.13A

\*Tolerance±8%

## Dimensions

