

ADVANCED HIGH CEILING

Lance 4 - Single Sided



High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a lumen package range from 1,314 lm to 2,160 lm. This IP 65 rated, single sided luminaire is available in a variety of configurations, and optics to help make a bold architectural statement.

Quantity		Type	
Project		Note	

Electrical System

- 1620 lm (20W)
- 2400 lm (30W)
- Power Input: Universal (120/277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

LED Technology

- 2700K, 3000K, 3500K, 4000K
- 85 CRI, 93 CRI
- Beam Angle: 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- TRIAC: Line-voltage phase control, dims to 1% (120V only)

Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

Warranty

- 5 year limited warranty

Listing

- ETL Wet Location Listed
- IP65



Lance 4 - Single Sided



How To Specify:

Ordering Example: LA4-D-20-408-UNV-SPV-35-BLK

4-5 weeks lead time on over 75% of specifications.

Model	Direction	Wattage	CCT / CRI	Voltage	Dimming
LA4				UNV	
LA4	D Down	20 20W	278 2700K / CRI85	UNV 120/277V	NOD Non-Dimming
Lance 4	U Up	30 30W	308 3000K / CRI85		STV Standard 0-10V dims to 10%
			358 3500K / CRI85		SPV Superior 0-10V dims to 1%
			408 4000K / CRI85		TRC TRIAC dims to 1% (120V ONLY)
			279 2700K / CRI93		
			309 3000K / CRI93		
			359 3500K / CRI93		

Beam Angle	Color	Finish	Accessories
30 30	BLK Black	OUT Outdoor	FW ¹ Forward Throw
45 45	WHT White	NAT Natatorium Rated	WW ¹ Wall Wash 20°
60 ¹ 60	GRY Gray	MAR Marine Finish	LL ¹ Linear Lens
WD ¹ WIDE	BRZ Bronze		HC ² Honeycomb Louver
			SL ³ Solite Lens
¹ Please factor in change in lumen output of -12%			¹ Please factor in change in lumen output of -20% ² Please factor in change in lumen output of -30%. ³ Please factor in change in lumen output of -15%.

Lance 4 - Single Sided

Delivered Lumens*

CCT	Wattage	
	20W	30 W
4000K	1458 lm	2160 lm
3500K	1414 lm	2098 lm
3000K	1368 lm	2034 lm
2700K	1314 lm	1944 lm

Current Consumption

Wattage	Volt	
	120V	277V
20W	0.2A	0.09A
30W	0.3A	0.13A

*Tolerance±8%

Dimensions

