

Lance 4 - White Up / Down



High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a combined lumen package range from 1,314 lm to 2,160 lm. Available in a variety of configurations, this IP 65 rated luminaire has a variety of optics to help make a bold architectural statement.

Quantity	Type
Project	Note

Electrical System

- 1,458 lm (20W) Uplight: 10W / Downlight: 10W
- 2,160 lm (30W) Uplight: 15W / Downlight: 15W
- Power Input: Universal (120/277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

LED Technology

- 2700K, 3000K, 3500K, 4000K
- 85 CRI, 93 CRI
- Beam Angle:
 - Down: 15°, 30°, 45°, 60°, WD
 - Up: 15°, 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- TRIAC: Line-voltage phase control, dims to 1% (120V only)

Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

Warranty

- 5 year limited warranty

Listing

- ETL Wet Location Listed
- IP65



Lance 4 - White Up / Down



How To Specify:

Ordering Example: LA4-20-408-UNV-SPV-3535-BLK

4-5 weeks lead time on over 75% of specifications.

Model	Wattage	CCT / CRI	Voltage	Dimming
LA4			UNV	
LA4	20 Downlight: 10W Uplight: 10W	278 2700K / CRI85	UNV 120/277V	NOD Non-Dimming
Lance4	30 Downlight: 15W Uplight: 15W	308 3000K / CRI85		STV Standard 0-10V dims to 10%
		358 3500K / CRI85		SPV Superior 0-10V dims to 1%
		408 4000K / CRI85		TRC TRIAC dims to 1% (120V ONLY)
		279 2700K / CRI93		
		309 3000K / CRI93		
		359 3500K / CRI93		

Beam Angle	Color	Finish	Accessories
Downlight	BLK Black	OUT Outdoor	FW² Forward Throw 20°
15	WHT White	NAT Natatorium Rated	WW² Wall Wash 20°
30	GRY Gray	MAR Marine Finish	LL² Linear Lens
45	BRZ Bronze		SL³ Solite Lens
60¹			
WD¹			
Uplight			
15			
30			
45			
60¹			
WD¹			

¹Please factor in change in lumen output of -12%

²Option only available with 30° Beam Angle. Please factor in change in lumen output of -20%

³Please factor in change in lumen output of -12%

Lance 4 - White Up / Down

Delivered Lumens*

CCT	20W		30W	
	UP (10W)	DOWN (10W)	UP (15W)	DOWN (15W)
4000K	729 lm	729 lm	1080 lm	1080 lm
3500K	707 lm	707 lm	1049 lm	1049 lm
3000K	684 lm	684 lm	1017 lm	1017 lm
2700K	657 lm	657 lm	972 lm	972 lm

Current Consumption

Wattage	Volt	
	120V	277V
20W	0.2A	0.09A
30W	0.3A	0.13A

*Tolerance±8%

Dimensions

