

# Lance 4 - White Up / Down



## High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a combined lumen package range from 1,314 lm to 2,160 lm. Available in a variety of configurations, this IP 65 rated luminaire has a variety of optics to help make a bold architectural statement.

Quantity	Type
Project	Note

### Electrical System

- 1,458 lm (20W) Uplight: 10W / Downlight: 10W
- 2,160 lm (30W) Uplight: 15W / Downlight: 15W
- Power Input: Universal (120/277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

### LED Technology

- 2700K, 3000K, 3500K, 4000K
- 85 CRI, 93 CRI
- Beam Angle:
  - Down: 15°, 30°, 45°, 60°, WD
  - Up: 15°, 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

### Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- TRIAC: Line-voltage phase control, dims to 1% (120V only)

### Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

### Warranty

- 5 year limited warranty

### Listing

- ETL Wet Location Listed
- IP65



# Lance 4 - White Up / Down



## How To Specify:

**Ordering Example: LA4-20-408-UNV-SPV-3535-BLK**

**4-5 weeks lead time on over 75% of specifications.**

Model	Wattage	CCT / CRI	Voltage	Dimming
LA4			UNV	
LA4	<b>20</b> Downlight: 10W Uplight: 10W	<b>278</b> 2700K / CRI85	<b>UNV</b> 120/277V	<b>NOD</b> Non-Dimming
Lance4	<b>30</b> Downlight: 15W Uplight: 15W	<b>308</b> 3000K / CRI85		<b>STV</b> Standard 0-10V dims to 10%
		<b>358</b> 3500K / CRI85		<b>SPV</b> Superior 0-10V dims to 1%
		<b>408</b> 4000K / CRI85		<b>TRC</b> TRIAC dims to 1% (120V ONLY)
		<b>279</b> 2700K / CRI93		
		<b>309</b> 3000K / CRI93		
		<b>359</b> 3500K / CRI93		

Beam Angle	Color	Finish	Accessories
Downlight	<b>BLK</b> Black	<b>OUT</b> Outdoor	<b>FW<sup>2</sup></b> Forward Throw 20°
<b>15</b>	<b>WHT</b> White	<b>NAT</b> Natatorium Rated	<b>WW<sup>2</sup></b> Wall Wash 20°
<b>30</b>	<b>GRY</b> Gray	<b>MAR</b> Marine Finish	<b>LL<sup>2</sup></b> Linear Lens
<b>45</b>	<b>BRZ</b> Bronze		<b>SL<sup>3</sup></b> Solite Lens
<b>60<sup>1</sup></b>			
<b>WD<sup>1</sup></b>			
Uplight			
<b>15</b>			
<b>30</b>			
<b>45</b>			
<b>60<sup>1</sup></b>			
<b>WD<sup>1</sup></b>			

<sup>1</sup>Please factor in change in lumen output of -12%

<sup>2</sup>Option only available with 30° Beam Angle. Please factor in change in lumen output of -20%

<sup>3</sup>Please factor in change in lumen output of -12%

# Lance 4 - White Up / Down

## Delivered Lumens\*

CCT	20W		30W	
	UP (10W)	DOWN (10W)	UP (15W)	DOWN (15W)
4000K	729 lm	729 lm	1080 lm	1080 lm
3500K	707 lm	707 lm	1049 lm	1049 lm
3000K	684 lm	684 lm	1017 lm	1017 lm
2700K	657 lm	657 lm	972 lm	972 lm

## Current Consumption

Wattage	Volt	
	120V	277V
20W	0.2A	0.09A
30W	0.3A	0.13A

\*Tolerance±8%

## Dimensions

