

ADVANCED HIGH CEILING

Lance 4 - White Up / Down



High Performing Outdoor Luminaire

Built to last, the Lance 4 is a 4-inch round outdoor wall mount cylinder with a combined lumen package range from 1,460 lm to 2,400 lm. Available in a variety of configurations, this IP 65 rated luminaire has a variety of optics to help make a bold architectural statement.

Quantity		Type	
Project		Note	

Electrical System

- 1620 lm (20W) Uplight: 10W / Downlight: 10W
- 2400 lm (30W) Uplight: 15W / Downlight: 15W
- Power Input: Universal (120-277V)
- Operating Temperature: 14°F~104°F
- Surge Protection: 2.5KV
- Power Factor Greater than 0.9

LED Technology

- 2700K, 3000K, 3500K, 4000K, NA
- 85 CRI, 93 CRI
- Beam Angle:
 - Down: 15°, 30°, 45°, 60°, WD
 - Up: 15°, 30°, 45°, 60°, WD
- Rated Life > 60,000 Hours (L70)

Advanced Dimming

(Proprietary VX Driver is incorporated to all dimming options for video flicker-free lighting)

- Standard 0-10V: dims to 10%
- Superior 0-10V: dims to 1%
- LTE: Hi-Lume 1% 2-wire LED Driver (120V forward phase only)

Housing

- Diameter: 4" (102mm)
- Height: 9.5" (240mm)
- Material: Aluminum
- Weight: 9.2 lbs

Warranty

- 5 year limited warranty

Listing

- ETL Wet Location Listed
- IP65



Lance 4 - White Up / Down



How To Specify:

Ordering Example: LA4-20-408-UNV-SPV-3535-BLK

4-5 weeks lead time on over 75% of specifications.

Model	Wattage	CCT / CRI	Voltage	Dimming
LA4			UNV	
LA4	20 Downlight: 10W Uplight: 10W	278 2700K / CRI85	UNV 120-277V	NOD Non-Dimming
Lance4	30 Downlight: 15W Uplight: 15W	308 3000K / CRI85		STV Standard 0-10V dims to 10%
		358 3500K / CRI85		SPV Superior 0-10V dims to 1%
		408 4000K / CRI85		LTE Hi-Lume 1% 2-wire LED Driver (120V forward phase only)
		279 2700K / CRI93		
		309 3000K / CRI93		
		359 3500K / CRI93		
	NOTE: Contact Factory for only downlight option			

Beam Angle	Color	Finish	Accessories
Downlight	BLK Black	OUT Outdoor Rated	FW ¹ Forward Throw
15 15	WHT White	NAT Natatorium Rated	WW ¹ Wall Wash 20°
30 30	GRY Gray	MAR Marine Finish	LL ¹ Linear Lens
45 45	BRZ Bronze		HC ² Honeycomb Louver
60 ¹ 60			SL ³ Solite Lens
WIDE ¹ WIDE			
Uplight			
15 15			
30 30			
45 45			
60 ¹ 60			
WIDE ¹ WIDE			
¹ Please factor in change in lumen output of -12%			² Please factor in change in lumen output of -30%. Honeycomb Louver applicable only to downlight.
			³ Please factor in change in lumen output of -15%.

Lance 4 - White Up / Down

Delivered Lumens*

CCT	Wattage	20W		30W	
		UP (10W)	DOWN (10W)	UP (15W)	DOWN (15W)
4000K		729 lm	729 lm	1080 lm	1080 lm
3500K		707 lm	707 lm	1049 lm	1049 lm
3000K		684 lm	684 lm	1017 lm	1017 lm
2700K		657 lm	657 lm	972 lm	972 lm

Current Consumption

Wattage	Volt	120V	277V
		20W	0.2A
30W		0.3A	0.13A

*Tolerance±8%

Dimensions

