

REV 8 PRIME

QUIET CEILING DESIGN HIGH LUMEN RECESSED DOWNLIGHT

Housing

Aperture : Ø9" | Oversize Trim : 9.13" | Ceiling Cutout : 8.25"
Maximum Ceiling Thickness : 1.5" | Height : 8.6"
Weight : 17.63 lbs/18.82 lbs (New Construction), 16.13 lbs (Retrofit)

Material

Housing : Forged Aluminum Heatsink
Reflector : Flow Forming Aluminum

Power Input

W+RGB :
200W TypeA(White=100W, RGB=100W) | 120-277V
200W TypeB(White=150W, RGB=50W) | 120-277V
W+Hue :
200W(White=132W, HSV=66W) | 120-277V

Lumen Output

W+RGB : 13,250 lm (200W TypeA), 14,145 lm (200W TypeB)
W+Hue : 16,050 lm (200W)

Dimming

DMX : High resolution dims to 0.1%

Color Quality	Rated Life
CRI 85	> 100,000 Hours (L70)


Finish



Color Temperature



Optics



Warranty

5 Year limited warranty

Listing




SPECIFICATION SHEET ARCHI-COLOR™ W+RGB & W+HUE

Precision Engineered For High Performance.

8-inch aperture high lumen recessed downlight utilizing Meteor Lighting's proprietary Archi-Color™ solution, that gives you True White light and unlimited RGB possibilities.

This product is compatible with all DMX control systems and follows ANSI E1.20 RDM protocol. You can now get white and RGB colors all from a single light source.



METEOR

meteor-lighting.com

SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

<input type="checkbox"/>	MODEL	R8PN REV 8 Prime with New Construction Frame	R8PR REV 8 Prime Retrofit
<input type="checkbox"/>	WATTAGE	200 200W	200A White=100W/RGB=100W 200B White=150W/RGB=50W
<input type="checkbox"/>	CCT / CRI	308C ¹ 3000K + RGB / CRI 85 Archi-Color™ W+RGB	308U ² 3000K + RGB / CRI 85 Archi-Color™ W+Hue
<input type="checkbox"/>	VOLTAGE	120 120V	277 277V
<input type="checkbox"/>	DIMMING	DMX DMX dims to 0.1% (XLR Sockets)	DMXR DMX dims to 0.1% (RJ45 Sockets)
<input type="checkbox"/>	BEAM ANGLE	45 45°	55 55°
<input type="checkbox"/>	FINISH*	BLK Black	WHT White
<input type="checkbox"/>	ACCESSORIES	DF ⁴ Diffuser GR14 ⁵ Goof Ring 9.2" to 16" SCA820 ⁷ Sloped Ceiling Adapter 18°-22°	SPD ⁵ Surge Protector SCA810 ⁷ Sloped Ceiling Adapter 8°-12° SCA825 ⁷ Sloped Ceiling Adapter 23°- 27° GR12 ⁶ Goof Ring 9.2" to 14" SCA815 ⁷ Sloped Ceiling Adapter 13°-17° 2CPL ⁸ 2' X 2' X 1" Custom Metal Ceiling Panel

 **CLEAR FORM**

¹ 308C is not compatible with 200

² 308U is not compatible with 200A, 200B

³ WD option reduces delivered lumens by ~20%

⁴ DF option reduces delivered lumens by ~12% (~20% with WD)

⁵ Surge protector for up to 10KV. Applicable for unstable mains or facilities using high power machineries

⁶ GR includes new reflector and is not compatible with R8PN

⁷ SCA is not compatible with R8PR

⁸ 2CPL is not compatible with R8PR, SCA810, SCA815, SCA820, SCA825

* Finish indicates trim only, with standard matte silver reflector

TECHNICAL DETAILS

Electrical

- Archi-Color™ W+RGB :
13,250 lm (200W TypeA | White = 100W, RGB = 100W)
14,145 lm (200W TypeB | White = 150W, RGB = 50W)
- Archi-Color™ W+Hue :
16,050 lm (200W | White = 132W, HSV = 66W)
- Power Input : 120V or 277V
- Operating Temperature : -40°F~112°F
- Surge Protection : Built-in is 4KV
- Power Factor Greater than 0.9

LED Features

- Color Temperature : 3000K+Archi-Color™ W+RGB / W+Hue
- CRI 85
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

Optics

- Flow Forming Aluminum Reflector
- Beam Angle : 45°, 55°, Wide (With diffuser)

Advanced Dimming

- Proprietary VX Driver™ is incorporated to all dimming options for video flicker-free lighting
- DMX : High resolution dims to 0.1% (Supports ANSI E1.20 RDM protocol)

New Construction Housing

- Aperture : Ø8.15" (New Construction), Ø9" (Retrofit)
- Height : 8.6"
- Weight : 17.63 lbs/18.82 lbs (New Construction), 16.13 lbs (Retrofit)
- Material : Forged Aluminum Heatsink
- Non-IC Rated, insulation must be kept >1ft from housing
- Oversize Trim : 8.46" (New Construction), 9.13" (Retrofit)
- Ceiling Cutout : 8.25"
- Maximum Ceiling Thickness : 1.5"
- Tool-less top access allows service from above and below
- Light engine, optics, and driver(s) accessible from below ceiling
- Goof Ring 14" : Aluminum, standard white finish; O. D. 16"; other size and finish available, please inquire

*Note : C-Channel / Mounting Channels / T-Bar Hangers are purchased from a third party

Warranty

- 5-year limited warranty

Listing

- ETL Damp Location Listed
- FCC
- CE
- UKCA

PERFORMANCE SUMMARY*

Lumen Performance (W+RGB)				
	R	G	B	W
200W TypeA	615lm	4,075lm	480lm	8,080lm
200W TypeB	220lm	1,700lm	210lm	12,015lm

Wattage (W+RGB)				
Channel Fixture Wattage	R	G	B	W
200W TypeA	33W	33W	33W	100W
200W TypeB	17W	17W	17W	150W

Lumen Performance (W+Hue)				
	R	G	B	W
200W	930lm	7,330lm	860m	8,720lm

Wattage (W+Hue)		
Channel Fixture Wattage	HSV*	W
200W	66W	132W


*Beam Angle: 45° * Tolerance ±8%

*The output power of any color generated through the three channels of HSV.


Current Consumption		
WATTAGE / VOLT	120V	227V
200W	1.8A	0.9A

PHOTOMETRICS


Below is a typical photometric representation of the Rev 8 Prime fixture. Please download IES files to ensure exact photometric value.



45°



55°



WIDE

DMX REQUIREMENTS


The Rev 8 Prime Archi-Color™ fixture with DMX is a **four channel dmx** unit. When placing an order, please indicate DMX address. (The DMX address will be listed on the back of the fixture). Do not connect more than 32 fixtures per DMX daisy chain.

DMX Address (W+RGB)				
Fixture	Red Control (ex. X)	Green Control (ex. X+1)	Blue Control (ex. X+2)	White Control (ex. X+3)
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

DMX Address (W+Hue)				
Fixture \ Channel	Hue (H)	Saturation (S)	Value / Intensity (V)	White Control (W)*
#1	1	2	3	4
#2	5	6	7	8
#3	9	10	11	12

The fixture can be connected with RJ45 or XLR sockets. DMX cables **are not** included; please refer to compatible DMX cabling list for more information. The final fixture on each daisy chain should be terminated by the use of a DMX terminator purchased from a 3rd party or from Meteor.

CONNECTION	RJ45 (CAT5e)	5-PIN XLR
Common	WHITE/BROWN(PIN7) & BROWN (PIN 8)	PIN 1
Signal -	ORANGE (PIN 2)	PIN 2
Signal +	WHITE/ORANGE (PIN 1)	PIN 3
Spare	-	PIN 4
Spare	-	PIN 5



COMPATIBLE DMX CABLING LIST

DMX uses a cable consisting of two twisted pairs plus a shield to carry data. The cable must be specifically impedance matched for the digital DMX signal, meaning that microphone cable or other non-rated cable **must not be used to carry DMX**. Network cable (Cat5, 5e or 6 cable) may be used to carry DMX in an installation; however special consideration must be given to shielding and termination. Under no circumstances should solid core cable like Cat5 be terminated into a screw down connector.

Meteor recommends the use of Belden 9729 or Belden 9841 for DMX installation. Belden 9729/9841 is a two pair cable, which allows for a spare pair for 'out and back' type terminations if needed.



COLOR TEMPERATURE CHART

This color temperature chart provides the precise values required to recreate specific color temperatures.

		Color Temperature Chart (W+Hue)			
Channel		1	2	3	4
Color/CCT		Hue (H)	Saturation (S)	Value / Intensity (V)	White Control (W)*
RED		0	255	255	0
GREEN		85	255	255	0
BLUE		170	255	255	0
1900K		16	255	255	90
2700K		22	255	255	200
3000K		28	255	255	255
3500K		42	225	255	255
4000K		70	165	255	255
4500K		85	150	255	255
5000K		120	215	255	255
6500K		132	255	255	237


*The White Control channel adjusts the brightness of 3000K LEDs.

DIMENSIONS




DIMENSIONS

Sloped Ceiling Adapter



Goof Ring 12



Goof Ring 14

